

Protocol converters

CANopen

PROFINET

eco

PROFIBUS


Modbus




ECO-510-PBUS-RTU



ECO-510-PBUS-CAN



ECO-510-PNET-CAN



ECO-510-PNET-RTU

Modbus - Profibus Profinet - CANopen

Full compatibility with Profinet, Profibus, Modbus RTU and CANopen protocols.
Easy configuration via Ethernet.
DIN Rail standard dimensions.

Main features

Box	DIN43880 – 4 module 71x90x64
Power supply	12..24 V DC +/- 15%
Power consumption	3 W
Operating conditions	Temperature 0-45 °C, humidity 35..95 RH%
Material	Noryl V0
Weight	Approx. 250 g
Sealing	IP20 box
Terminal blocks	Extractable

Programming tool

Configuration Tool available on www.pixsys.net www.remberg.es

The screenshot shows the 'Set Translate Table' application window. It contains a table with the following columns: N°, Data Type, Address TCP, Address Device RTU, Address RTU, N° Point, and Mnemonic. The first two rows are populated with data:

N°	Data Type	Address TCP	Address Device RTU	Address RTU	N° Point	Mnemonic
1	Holding Register	100	5	200	1	Temperature
2	Input Register	150	5	234	1	SetPoint
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						
21						
22						
23						
24						
25						
26						
27						

Overlaid on this is the 'General Parameter' dialog box. It has the following settings:

- Operation Mode:** Routing Mode, NAT Mode
- MODBUS TCP:**
 - IP Address: 0 . 0 . 0 . 0
 - Subnet Mask: 255 . 255 . 255 . 0
 - Enable Gateway
 - Gateway: 0 . 0 . 0 . 0
 - Port: 502
- MODBUS RTU:**
 - Baud rate: 9600
 - Parity: NONE
 - Timeout (ms): 1000
- System Data Offset:** 10000

Ordering codes

ECO-510-PBUS-RTU	Protocol converter Modbus RTU - Profibus
ECO-510-PBUS-CAN	Protocol converter CANOpen - Profibus
ECO-510-PNET-CAN	Protocol converter CANOpen - Profinet
ECO-510-PNET-RTU	Protocol converter Modbus RTU - Profinet